

Cold Asphalt Patching/Paving Material

Contains: Limestone 90% TO 100%; Quartz < 1%; Asphalt < 10%; Hydrogen sulfide < 0.1%; Fuels, diesel, No. 2 0% TO 4%; Naphthalene < 0.004%; Kerosene 0% TO 4%; Kerosine, hydrodesulfurized 0% TO 4%; Additives < 0.5%

Vendor Product Code(s): SDS number: HMC-1009

According to OSHA 29 CFR 1910.1200 HCS



DANGER

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May cause cancer.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water .

Take off contaminated clothing and wash before reuse.

Specific treatment, see supplemental first aid information.

If skin irritation or rash occurs: Get medical advice/attention.

IF exposed or concerned: Get medical advice/attention.

Store locked up.

Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Please refer to the SDS for additional information.

Hudson Materials Company, 1615 Sholar Avenue Chattanooga, TN 37406 United States, General Information:
(423) 624-2631 ; Emergency: 1-800-633-8253 PERS.